



POWERED BY SALSIFY

**Americas PDS Database** > **CRC 3-36 Multi-Purp Lubricant & Corrosion Inhibitor**

---



# CRC 3-36 Multi-Purp Lubricant & Corrosion Inhibitor

## ATTRIBUTES

---

### Item Number

1003255

### Legacy Number

03005

### Case Number

1003254

### Product Description

A versatile petroleum based compound that forms a clear, thin film that lubricates and protects against wear and corrosion. Multi-purpose product lubricates, protects, displaces moisture, and cleans.

### Applications

Tubing, castings, gears, weld rod, wire, fixtures, dies, jigs, shim stock, chucks, drill rod, heat treated parts, machined surfaces, finished welds, aluminum extrusions, air actuated tools, conveyors, frozen joints, locks, hoists, etc.

**Unit Package Description**

16 Ounce Aerosol

**Brand**

CRC

**Net Fill**

11 Wt Oz

**Unit Dimensions**

7.75H x 2.63W x 2.63D in

**Units Per Case**

12

**UPC Code**

78254030050

**Case Dimensions**

8.1H x 8.3W x 11.1D in

**Appearance**

Clear Blue-Green Liquid

**Base Type**

Petroleum

**Flash point (F)**

192°F

**Flash point (C)**

89°C

**Flammability Class - CPSC**

Flammable

**KB Value**

N/A

**Plastic Safe**

No

**Film Type**

Non-Drying

**Film Thickness**

0.025 to 0.075 Mils

**Evaporation Rate**

Slow

**Dielectric Strength**

38,800 Volts

**Timken Ok Load (lbs)**

N/A

**Propellant**

Carbon Dioxide

**NSF Category Code**

H2

**NSF Number**

017411

**Aerosol Flammability Level**

III

**DOT Proper Shipping Name**

Aerosols, Flammable, Limited Quantity

**4 Ball EP**

Not Determined

**4 Ball Wear**

Not Determined

**Drop Point**

N/A

**pH**

N/A

**SAE Grade**

N/A

**Water Washout**

N/A

**Working Temp (F)**

-50 to 250°F

**Working Temp (C)**

-45.6 to 121.1°C

**VOC % (Consumer Product def)**

0

**VOC g/L (Consumer Product def)**

0

**VOC lbs/gal (Consumer Prod def)**

0

**VOC Category**

Multi-Purpose Lubricant

**Removal (How To)**

Remove with petroleum products, mineral spirits, or contact cleaner.