



POWERED BY S A L S I F Y

Americas PDS Database > **CRC 3-36 Multi-Purp Lubricant & Corrosion Inhibitor**



CRC 3-36 Multi-Purp Lubricant & Corrosion Inhibitor

ATTRIBUTES

Item Number

1003262

Legacy Number

03011

Product Description

A versatile petroleum based compound that forms a clear, thin film that lubricates and protects against wear and corrosion. Multi-purpose product lubricates, protects, displaces moisture, and cleans.

Applications

Tubing, castings, gears, weld rod, wire, fixtures, dies, jigs, shim stock, chucks, drill rod, heat treated parts, machined surfaces, finished welds, aluminum extrusions, air actuated tools, conveyors, frozen joints, locks, hoists, etc.

Unit Package Description

55 Gallon Drum

Brand

CRC

Net Fill

55 Gal

Unit Dimensions

35H x 24.5W x 24.5D in

Units Per Case

1

UPC Code

78254030111

Case Dimensions

35H x 24.5W x 24.5D in

Appearance

Clear Blue-Green Liquid

Base Type

Petroleum

Flash point (F)

192°F

Flash point (C)

89°C

Flammability Class - CPSC

None

KB Value

N/A

Plastic Safe

No

Film Type

Non-Drying

Film Thickness

0.025 to 0.075 Mils

Evaporation Rate

Slow

Dielectric Strength

38,800 Volts

Timken Ok Load (lbs)

N/A

Propellant

None

NSF Category Code

H2

NSF Number

017429

DOT Proper Shipping Name

Not Regulated

4 Ball EP

Not Determined

4 Ball Wear

Not Determined

Drop Point

N/A

pH

N/A

SAE Grade

N/A

Water Washout

N/A

Working Temp (F)

-50 to 250°F

Working Temp (C)

-45.6 to 121.1°C

VOC % (Consumer Product def)

0

VOC g/L (Consumer Product def)

0

VOC lbs/gal (Consumer Prod def)

0

VOC Category

Multi-Purpose Lubricant

Removal (How To)

Remove with petroleum products, mineral spirits, or contact cleaner.