# SAFETY DATA SHEET

# 1. Identification

Other means of identification

**Part Number** 40010, 84005, 84205

Synonyms FORMULA CODE(S): \* A790M (Orange)

Recommended use Solvent based marker

**Recommended restrictions** None known.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Company name ITW Pro Brands

Address 805 E. Old 56 Highway

Olathe, KS 66061

Country (U.S.A.)

Tel: +1 800-443-9536

In Case of Emergency 1-800-535-5053 (Infotrac)

# 2. Hazard(s) identification

Physical hazards Flammable liquids Category 3

Health hazards Specific target organ toxicity, single exposure Category 3 narcotic effects

Environmental hazards Not classified.

OSHA defined hazards Not classified.

Label elements



Signal word Warning

Hazard statement Flammable liquid and vapor. May cause drowsiness or dizziness.

**Precautionary statement** 

Prevention Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly

closed. Ground/bond container and receiving equipment. Use explosion-proof

electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing mist or vapor. Use only outdoors or in a

well-ventilated area.

**Response** If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell. In case of fire: Use appropriate media to extinguish.

Storage Keep cool. Store in a well-ventilated place. Keep container tightly closed. Store locked up.

**Disposal** Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise

classified (HNOC)

None known.

Supplemental information None.

# 3. Composition/information on ingredients

#### **Mixtures**

Chemical name	Common name and synonyms	CAS number	%
Butyl Acetate		123-86-4	40 - 50
Propylene glycol monomethyl ether acetate		108-65-6	10 - 20

 Chemical nameCommon name and synonymsCAS number%Aromatic Solvent64742-95-60.1 - 1

#### 4. First-aid measures

Inhalation

Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON

CENTER or doctor/physician if you feel unwell.

Skin contact Take off immediately all contaminated clothing. Rinse skin with water/shower. Get medical

attention if irritation develops and persists.

Eye contact Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if

present and easy to do. Get medical attention if irritation develops and persists.

**Ingestion** Rinse mouth. Get medical attention if symptoms occur.

Most important symptoms/effects, acute and delayed

May cause drowsiness and dizziness. Headache. Nausea, vomiting. Direct contact with eyes may cause temporary irritation.

Indication of immediate medical attention and special

treatment needed

Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim under observation.

Symptoms may be delayed.

General information

Take off all contaminated clothing immediately. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance.

Wash contaminated clothing before reuse.

# 5. Fire-fighting measures

Suitable extinguishing media Unsuitable extinguishing media Water fog. Alcohol resistant foam. Dry chemical powder. Dry sand. Carbon dioxide (CO2).

Water. Do not use water jet as an extinguisher, as this will spread the fire. Carbon dioxide (CO2).

Specific hazards arising from the chemical

Vapors may form explosive mixtures with air. Vapors may travel considerable distance to a source of ignition and flash back. During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire fighting equipment/instructions

In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.

Specific methods

Use standard firefighting procedures and consider the hazards of other involved materials.

General fire hazards

Flammable liquid and vapor.

#### 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Take precautionary measures against static discharge. Use only non-sparking tools. This material is classified as a water pollutant under the Clean Water Act and should be prevented from contaminating soil or from entering sewage and drainage systems which lead to waterways.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water.

Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. Put material in suitable, covered, labeled containers. For waste disposal, see section 13 of the SDS.

#### **Environmental precautions**

Avoid discharge into drains, water courses or onto the ground.

# 7. Handling and storage

#### Precautions for safe handling

Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. When using do not smoke. Explosion-proof general and local exhaust ventilation. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Avoid breathing mist or vapor. Avoid prolonged exposure. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

# Conditions for safe storage, including any incompatibilities

Store locked up. Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a cool, dry place out of direct sunlight. Store in original tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

# 8. Exposure controls/personal protection

# Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

Components	r Contaminants (29 CFR 1910.1000) Type	Value	
Butyl Acetate (CAS 123-86-4)	PEL	710 mg/m3	
		150 ppm	
US. ACGIH Threshold Limit Value	<b>9</b> S		
Components	Туре	Value	
Butyl Acetate (CAS 123-86-4)	STEL	150 ppm	
	TWA	50 ppm	
US. NIOSH: Pocket Guide to Che	mical Hazards		
Components	Туре	Value	
Butyl Acetate (CAS 123-86-4)	STEL	950 mg/m3	
		200 ppm	
	TWA	710 mg/m3	
		150 ppm	
US. Workplace Environmental Ex	posure Level (WEEL) Guides		
Components	Туре	Value	
Propylene glycol monomethyl ether acetate (CAS 108-65-6)	TWA	50 ppm	

**Biological limit values** 

No biological exposure limits noted for the ingredient(s).

**Exposure guidelines** 

US - California OELs: Skin designation

Propylene glycol monomethyl ether acetate

Can be absorbed through the skin.

(CAS 108-65-6)

Appropriate engineering

controls

Explosion-proof general and local exhaust ventilation. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment

**Eye/face protection** Wear safety glasses with side shields (or goggles).

Skin protection

**Hand protection** Wear appropriate chemical resistant gloves.

**Other** Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.

Respiratory protection Use a positive-pressure air-supplied respirator if there is any potential for an uncontrolled release,

exposure levels are not known, or any other circumstances where air-purifying respirators may not

provide adequate protection.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Observe any medical surveillance requirements. When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove

contaminants.

# 9. Physical and chemical properties

**Appearance** 

Liquid. Physical state Liquid. **Form** Color Orange. Odor Sweet.

Not available. Odor threshold Not available. pН Melting point/freezing point Not available.

Initial boiling point and boiling

251.96 °F (122.2 °C)

range

81.0 °F (27.2 °C) Tag Closed Cup Flash point

**Evaporation rate** Not available. Flammability (solid, gas) Not applicable. Upper/lower flammability or explosive limits

1.7 % Flammability limit - lower

(%)

Flammability limit - upper

(%)

7.6 %

Explosive limit - lower (%) Not available. Not available. Explosive limit - upper (%) Vapor pressure Not available. Not available. Vapor density Not available. Relative density

Solubility(ies)

Not available. Solubility (water) Not available. **Partition coefficient** 

(n-octanol/water)

**Auto-ignition temperature** Not available. Not available. **Decomposition temperature Viscosity** Not available.

Other information

Not explosive. **Explosive properties** Not oxidizing. Oxidizing properties

VOC A719M Yellow: 68.20%, 716 g/L

A788M Blue: 68.83%, 694 g/L; A946M Gold: 59.75%, 689 g/L A789M Green: 69.77%, 725 g/L; A787M Pink: 48.62%, 637 g/L A783M Light Blue: 50.34%, 588 g/L; A790M Orange: 65.48%, 647 g/L A791M Red: 66.17%, 671 g/L; A785M Violet: 76.57%, 771 g/L A945M Silver: 71.68%, 714 g/L; A718M White: 47.85%, 627 g/L A720M Black: 66.61%, 672 g/L; A786M Brown: 67.78%, 712 g/L

# 10. Stability and reactivity

The product is stable and non-reactive under normal conditions of use, storage and transport. Reactivity

**Chemical stability** Material is stable under normal conditions. Possibility of hazardous

reactions

Hazardous polymerization does not occur.

Conditions to avoid

Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the

flash point. Contact with incompatible materials.

Incompatible materials

Acids. Strong oxidizing agents. Chlorine. Isocyanates. Nitrates.

Hazardous decomposition products

Carbon oxides.

# 11. Toxicological information

Information on likely routes of exposure

Inhalation May cause drowsiness and dizziness. Headache. Nausea, vomiting. Prolonged inhalation may be

harmful.

Skin contact No adverse effects due to skin contact are expected. Direct contact with eyes may cause temporary irritation. Eye contact

Ingestion Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics May cause drowsiness and dizziness. Headache. Nausea, vomiting.

Information on toxicological effects

**Acute toxicity** Not expected to be acutely toxic.

Components **Species Test Results** 

Aromatic Solvent (CAS 64742-95-6)

**Acute Dermal** 

LD50 Rabbit > 1900 mg/kg, 24 Hours

Inhalation Vapor

Rat LC50 > 5 mg/l, 4 Hours

Oral

LD50 Rat 4800 mg/kg

Butyl Acetate (CAS 123-86-4)

Acute Inhalation

LC50 Rat 1.8 mg/l, 4 Hours

Oral

Rat LD50 14000 mg/kg

Propylene glycol monomethyl ether acetate (CAS 108-65-6)

**Acute Dermal** 

LD50 Rat > 2000 mg/kg, 24 Hours

Oral

LD50 Rat > 5000 mg/kg

Prolonged skin contact may cause temporary irritation. Skin corrosion/irritation Serious eye damage/eye

irritation

Direct contact with eyes may cause temporary irritation.

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization This product is not expected to cause skin sensitization.

Germ cell mutagenicity No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.

IARC Monographs. Overall Evaluation of Carcinogenicity

Not listed.

# OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not classified.

Not listed

US. National Toxicology Program (NTP) Report on Carcinogens

Not listed.

**Reproductive toxicity**This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

May cause drowsiness and dizziness.

Specific target organ toxicity -

repeated exposure

**Aspiration hazard** Not an aspiration hazard.

**Chronic effects** Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects.

**Further information** Symptoms may be delayed.

12. Ecological information

**Ecotoxicity**The product is not classified as environmentally hazardous. However, this does not exclude the

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Components Species Test Results

Butyl Acetate (CAS 123-86-4)

Aquatic

Fish LC50 Fathead minnow (Pimephales promelas) 17 - 19 mg/l, 96 hours

**Persistence and degradability** No data is available on the degradability of any ingredients in the mixture.

**Bioaccumulative potential** 

Partition coefficient n-octanol / water (log Kow)

Butyl Acetate 1.78

Mobility in soil Not established.

Other adverse effects None known.

13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of

contents/container in accordance with local/regional/national/international regulations.

**Local disposal regulations**Dispose in accordance with all applicable regulations.

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

# 14. Transport information

DOT

**UN number** UN1263

UN proper shipping name Paint, MARINE POLLUTANT (Copper, Copper Compounds)

Transport hazard class(es)

Class 3
Subsidiary risk Label(s) 3
Packing group III

**Environmental hazards** 

Marine pollutant Yes

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Special provisions B1, B52, IB3, T2, TP1, TP29

Packaging exceptions 150
Packaging non bulk 173
Packaging bulk 242

Material name: Dykem® Brite-Mark® - Orange

40010, 84005, 84205 Version #: 01 Issue date: 10-29-2019

) - Orange

#### **IATA**

**UN** number UN1263 Paint UN proper shipping name

Transport hazard class(es)

Class 3 Subsidiary risk **Packing group** Ш **Environmental hazards** Yes **ERG Code** 3L

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Other information

Passenger and cargo

Allowed with restrictions.

aircraft

Class

Allowed with restrictions. Cargo aircraft only

**IMDG** 

UN1263 **UN number** PAINT, MARINE POLLUTANT (Copper, Copper Compounds)

UN proper shipping name Transport hazard class(es)

3 Subsidiary risk Packing group Ш

**Environmental hazards** 

Yes Marine pollutant F-E, S-E **EmS** 

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Copper, Copper Compounds

Transport in bulk according to Annex II of MARPOL 73/78 and Not applicable.

the IBC Code

# DOT



IATA; IMDG



# Marine pollutant



General information IMDG Regulated Marine Pollutant. DOT Regulated Marine Pollutant.

# 15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

# **Toxic Substances Control Act (TSCA)**

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

#### **CERCLA Hazardous Substance List (40 CFR 302.4)**

Butyl Acetate (CAS 123-86-4) Listed.

# SARA 304 Emergency release notification

Not regulated.

# OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

# Superfund Amendments and Reauthorization Act of 1986 (SARA)

# SARA 302 Extremely hazardous substance

Not listed.

Classified hazard Flammable (gases, aerosols, liquids, or solids)

categories Specific target organ toxicity (single or repeated exposure)

# SARA 313 (TRI reporting)

Not regulated.

# Other federal regulations

#### Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

# Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Contains component(s) regulated under the Safe Drinking Water Act.

(SDWA)

#### FEMA Priority Substances Respiratory Health and Safety in the Flavor Manufacturing Workplace

Butyl Acetate (CAS 123-86-4) Low priority

# **US state regulations**

# US. New Jersey Worker and Community Right-to-Know Act

Butyl Acetate (CAS 123-86-4)

#### California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 2016 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

# US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

Aromatic Solvent (CAS 64742-95-6)

# **International Inventories**

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No

Country(s) or region	Inventory name	On inventory (yes/no)*
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes

(PICCS)

Taiwan Chemical Substance Inventory (TCSI)

United States & Puerto Rico

Toxic Substances Control Act (TSCA) Inventory

Yes

Philippine Inventory of Chemicals and Chemical Substances

# 16. Other information, including date of preparation or last revision

**Issue date** 10-29-2019

Version # 01

**Philippines** 

Disclaimer ITW Pro Brands cannot anticipate all conditions under which this information and its product, or

the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless

specified in the text.

**Revision information** Product and Company Identification: Product and Company Identification

Material name: Dykem® Brite-Mark® - Orange

40010, 84005, 84205 Version #: 01 Issue date: 10-29-2019

Yes

<sup>\*</sup>A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).