

REDUCED SHANK DRILL



General Purpose Reduced Shank - 3/4" Shank

R58 Silver & Deming Drills. Steam tempered for increased wear resistance & lubricity



R58

ANSI

1.5XD

HSS

118°



1" - 2"

d ₁ Ø Inch	d ₁ decimal Inch	l ₂ Inch	l ₁ Inch	d ₂ Ø Inch	Pack Qty	R58
1"	1.0000	3"	6"	3/4"	1	6000049
1.1/32	1.0312	3"	6"	3/4"	1	6000058
1.1/16	1.0625	3"	6"	3/4"	1	6000052
1.3/32	1.0937	3"	6"	3/4"	1	6000092
1.1/8	1.1250	3"	6"	3/4"	1	6000064
1.5/32	1.1563	3"	6"	3/4"	1	6000111
1.3/16	1.1875	3"	6"	3/4"	1	6000089
1.7/32	1.2187	3"	6"	3/4"	1	6000126
1.1/4	1.2500	3"	6"	3/4"	1	6000061
1.9/32	1.2813	3"	6"	3/4"	1	6000143
1.5/16	1.3125	3"	6"	3/4"	1	6000107
1.11/32	1.3437	3"	6"	3/4"	1	6000070
1.3/8	1.3750	3"	6"	3/4"	1	6000102
1.13/32	1.4063	3"	6"	3/4"	1	6000077
1.7/16	1.4375	3"	6"	3/4"	1	6000118
1.15/32	1.4687	3"	6"	3/4"	1	6000086
1.1/2	1.5000	3"	6"	3/4"	1	6000054
1.9/16	1.5625	3"	6"	3/4"	1	6000138
1.5/8	1.6250	3"	6"	3/4"	1	6000114
1.11/16	1.6875	3"	6"	3/4"	1	6000067
1.3/4	1.7500	3"	6"	3/4"	1	6000096
1.13/16	1.8125	3"	6"	3/4"	1	6000074
1.7/8	1.8750	3"	6"	3/4"	1	6000131
1.15/16	1.9375	3"	6"	3/4"	1	6000083
2"	2.0000	3"	6"	3/4"	1	6000147